

LITHCO MATERIAL SAFETY DATA SHEET

SECTION I: PRODUCT IDENTIFICATION

TRADE NAME (as labeled) Aerosol Ink Fresh

MANUFACTURER'S NAME: Lithco, Inc. • 9449 Jefferson Blvd. • Culver City, CA 90232-2913

PHONE NUMBER FOR ADDITIONAL INFORMATION: (310) 559-7770 or (800) 454-8426

FAX NUMBER FOR ADDITIONAL INFORMATION: (310) 559-6908 or (888) 454-8426

EMERGENCY INFORMATION: For chemical emergency, spill, leak, fire, exposure or accident call Infotrac, day or night, at (800) 535-5053.

DATE PREPARED OR REVISED: 7-5-02 (Replaces 10-1-01)

PREPARED BY (optional):

SECTION II: HAZARDOUS INGREDIENTS

			EXPOSURE LIMITS		
Chemical Names	CAS Numbers	%	ACGIH TLV	OSHA PEL	OTHER
Isoparaffinic Solvent	64742-47-8	15-25	300 ppm	N.E.	N/A
Hexane	110-54-3	10-20	50 ppm	50 ppm	N/A
2,6-di-tert-butyl-p-cresol	128-37-0	5-15	10 mg/m ³	10 mg/m ³	N/A
Isopropyl Alcohol	67-63-0	10-20	400 ppm	400 ppm	N/A
Hydrocarbon propellant	68476-85-7	40-50	100 ppm	1000 ppm	N/A

HMS RATING:

Health: 1

Fire: 4

Reactivity: 1

Personal protection: B

SECTION III: PHYSICAL PROPERTIES

VAPOR DENSITY (AIR = 1): >1.0

MELTING POINT/RANGE: N.D.

SPECIFIC GRAVITY: <1

BOILING POINT/RANGE: N/A °F

SOLUBILITY IN WATER: moderate

EVAPORATION RATE (Ether = 1): <1

VAPOR PRESSURE, (psig): 140 @ 130°F

APPEARANCE AND ODOR: Aerosol, clear liquid, mild oily odor

This product contains 3.84 lb./gal. VOC.

This product is not photochemically reactive.

SECTION IV: FIRE AND EXPLOSION

FLASH POINT, degrees F. (give method): This product is considered to be extremely flammable as described in 16CFR1500.45.

AUTO-IGNITION TEMPERATURE, degrees F.: N.D.

FLAMMABLE LIMITS IN AIR (VOLUME %), LOWER 1.8 % UPPER 9.2 %

FIRE EXTINGUISHING MATERIALS:

WATER SPRAY: NO	FOAM: XX	CARBON DIOXIDE: XX	DRY CHEMICAL: XX	OTHER: N/A
-----------------	----------	--------------------	------------------	------------

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighting personnel should wear full bunker gear with NIOSH approved SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool exposed containers with water fog to prevent explosions.

This form complies with and is essentially similar to OSHA Form 174 as specified in 29CFR 1910.1200 (Federal OSHA Hazard Communication Standard) and complies with requirements of CAL/OSHA.

SECTION V: HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE FOR EACH POTENTIAL ROUTE OF EXPOSURE

INHALED: Headache, dizziness, nausea.

CONTACT WITH SKIN OR EYES: Redness and irritation of skin and eyes. Burning of eyes.

ABSORBED THROUGH SKIN: Not a likely route of exposure.

SWALLOWED: Not a likely route of exposure.

HEALTH EFFECTS OR RISKS FROM EXPOSURE (Explain in lay terms)

ACUTE: Headache, dizziness, nausea, redness of skin and eyes, burning of eyes.

CHRONIC: None known.

FIRST AID EMERGENCY PROCEDURES

EYE CONTACT: Flush eyes for at least 15 minutes with running water while holding eyelids open. Get medical attention.

SKIN CONTACT: Remove contaminated clothing. Wash affected area with soap and water. Seek medical attention if irritation persists. Do not wear contaminated clothing until properly laundered.

INHALED: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration or CPR if not breathing. Seek medical attention.

SWALLOWED: Do not induce vomiting. If vomiting occurs, keep victim's below hips to prevent aspiration into lungs. Aspiration may cause aspiration pneumonitis, often evidenced by difficulty breathing, severe coughing and cyanosis (bluish skin). Seek immediate medical attention.

SUSPECTED CANCER AGENT?

XXX NO. THIS PRODUCT'S INGREDIENTS ARE NOT FOUND IN THE LISTS BELOW.

YES. FEDERAL OSHA NTP IARC

California employers using CAL/OSHA regulated carcinogens must register with CAL/OSHA. The CAL/OSHA and Federal OSHA carcinogen lists are similar.

CALIFORNIA PROP. 65 STATEMENT

THIS PRODUCT DOES NOT CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR CAUSE REPRODUCTIVE HARM.

PRE-EXISTING MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing eye, skin or upper respiratory conditions.

SECTION VI: REACTIVITY DATA

PRODUCT IS XXX STABLE _____ UNSTABLE

CONDITIONS TO AVOID: Avoid contact with heat, sparks and open flame. Do not store above 130°F or in direct sunlight. Dropping containers may cause bursting.

INCOMPATIBILITY (materials to avoid): Strong oxidizing agents, sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS, INCLUDING COMBUSTION: Carbon monoxide, carbon dioxide and unburned hydrocarbons

HAZARDOUS POLYMERIZATION _____ MAY OCCUR XXX WILL NOT OCCUR.

CONDITIONS TO AVOID: None under normal product use.

SECTION VII: SPILL, LEAK AND DISPOSAL PROCEDURES

SPILL RESPONSE PROCEDURES, INCLUDING EMPLOYEE PROTECTION: Extinguish all sources of ignition. Contain spill. Wear SCBA for airborne concentrations above TLV. Use sparkproof tools during clean-up. Soak up with inert absorbent.

PREPARING WASTES FOR DISPOSAL (containers, neutralization, etc.): Place in non-leaking containers suitable for material and certified for transporting hazardous waste.

NOTE: DISPOSE OF ALL WASTES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION VIII: SPECIAL HANDLING INFORMATION

VENTILATION AND ENGINEERING CONTROLS: Provide ventilation to keep airborne concentration below TLV.

RESPIRATORY PROTECTION (TYPE): NIOSH/MCA approved for organic vapors for concentrations above TLV.

EYE PROTECTION (TYPE): Splashproof chemical goggles.

GLOVES (SPECIFY MATERIAL): Neoprene, nitrile or PVC.

OTHER CLOTHING AND EQUIPMENT: Eyewash station and safety shower should be provided.

WORK PRACTICES, HYGIENIC PRACTICES: Wash hands thoroughly after use and before eating, drinking, smoking or using the toilet.

OTHER HANDLING AND STORAGE REQUIREMENTS: Keep containers closed when not in use. Do not use near sources of ignition. Avoid prolonged or repeated contact with skin or breathing of vapors. Keep from children. For industrial use only.

PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Use protective gear as indicated above. Do not start electrical equipment in presence of vapors.

SECTION IX: SHIPPING INFORMATION

FULL DOT SHIPPING NAME: Consumer Commodity

DOT HAZARD CLASS: ORM-D **PACKING GROUP:** N/A

UN/NA NUMBER: None

SECTION X: ENVIRONMENTAL STATEMENT

THIS PRODUCT IS SUBJECT TO REPORTING ACCORDING TO SARA, TITLE III (SUPERFUND AMENDMENT), SEC. 313. The reportable component is Hexane.

SECTION XI: APPENDIX

WORKPLACE CLASSIFICATION: This product is considered non-hazardous under the OSHA Hazard Communication Standard, 29CFR 1910.1200.

CERCLA INFORMATION (40CFR 302.4): Releases of this material into air, land or water are reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304. See above, Section X.

RCRA INFORMATION (40CFR 261): When this product becomes a waste, it is classified as a non-hazardous waste under criteria of the Resource Conservation and Recovery Act.

CHEMICAL CONTROL LAW STATUS: All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

CAUTION: CONTENTS UNDER PRESSURE. DO NOT PUNCTURE. FOLLOW DIRECTIONS ON LABEL. THIS PRODUCT CAN BE HAZARDOUS TO YOUR HEALTH OR FATAL IF INTENTIONALLY MISUSED.

Information contained in this safety data sheet is drawn from recognized sources and is believed to be accurate and correct as of the date of issue. It is presented for your evaluation of the suitability of the product and for compliance with federal and state regulations. No claims are made for the accuracy, completeness and reliability of the information contained herein.